

TEMA: 0115 ATP - (CHAP. 04) PERFORMANCE

COD_PREG: PREGUNTA:

8117 What is the maximum landing distance that may be used by a turbopropeller-powered, small transport category airplane to land on Rwy 24 (dry) at the alternate airport?

RPTA:
C

OPCION A: 5,490 feet.

OPCION B: 6,210 feet.

OPCION C: 6,405 feet.

8118 What is the maximum landing distance that may be used by a reciprocating-engine-powered, small transport category airplane to land on Rwy 24 (dry) at the destination airport?

A

OPCION A: 5,490 feet.

OPCION B: 6,210 feet.

OPCION C: 6,405 feet.

8119 What is the maximum landing distance that may be used by a turbopropeller-powered, small transport category airplane to land on Rwy 6 (dry) at the alternate airport?

C

OPCION A: 5,460 feet.

OPCION B: 6,210 feet.

OPCION C: 6,370 feet.

8120 What is the maximum landing distance that may be used by a reciprocating-engine-powered, small transport category airplane to land on Rwy 6 (dry) at the destination airport?

A

OPCION A: 5,460 feet.

OPCION B: 6,210 feet.

OPCION C: 6,370 feet.

8121 What is the maximum landing distance that may be used by a turbine-engine-powered, small transport category airplane to land on Rwy 24 (dry) at the destination airport?

B

OPCION A: 5,460 feet.

OPCION B: 5,490 feet.

OPCION C: 6,210 feet.

8122 What is the maximum landing distance that may be used by a turbine-engine-powered, small transport category airplane to land on Rwy 6 (wet) at the destination airport?

A

OPCION A: 5,460 feet.

OPCION B: 5,880 feet.

OPCION C: 6,088 feet.

8123 What is the maximum landing distance that may be used by a turbopropeller-powered, small transport category airplane to land on Rwy 19 (dry) at the destination airport?

C

OPCION A: 6,020 feet.

OPCION B: 5,820 feet.

OPCION C: 5,160 feet.

8124 What is the maximum landing distance that may be used by a reciprocating-engine-powered, small transport category airplane to land on Rwy 1 (dry) at the destination airport?

A

OPCION A: 5,010 feet.

OPCION B: 5,820 feet.

OPCION C: 5,845 feet.

8125 What is the maximum landing distance that may be used by a turbine-engine-powered, small transport category airplane to land on Rwy 1 (dry) at the destination airport?

A

OPCION A: 5,010 feet.

OPCION B: 5,820 feet.

OPCION C: 5,845 feet.

8126 What is the maximum landing distance that may be used by a turbine-engine-powered, small transport category airplane to land on Rwy 19 (dry) at the destination airport? A

OPCION A: 5,160 feet.

OPCION B: 5,820 feet.

OPCION C: 6,020 feet.

8127 May a small transport category, turbine-engine-powered airplane that has a computed landing distance of 5,500 feet use one or both of the runways depicted in the illustration at the destination airport? A

OPCION A: Neither Rwy 1 nor Rwy 19 may be used if dry conditions exist.

OPCION B: Only Rwy 19 may be used provided dry conditions exist.

OPCION C: Rwy 1 or Rwy 19 may be used whether conditions are wet or dry.

8128 May a small transport category, turboprop airplane that has a computed landing distance of 6,000 feet use either or both runways depicted in the illustration at the destination airport? B

OPCION A: Only Rwy 19 may be used if dry conditions exist.

OPCION B: Neither Rwy 1 nor Rwy 19 may be used under any conditions.

OPCION C: Either Rwy 1 or Rwy 19 may be used whether conditions are wet or dry.

8129 What is the maximum landing distance that may be used for a non-transport category, turbopropeller-driven airplane to land on Rwy 1 (dry) at the alternate airport? B

OPCION A: 5,010 feet.

OPCION B: 5,845 feet.

OPCION C: 6,020 feet.

8130 Which condition meets FAR Part 135 operational requirements for a small, transport category, turboprop airplane to land at the destination airport that has the runway environment given in the illustration? A

OPCION A: The airport may be listed as the destination airport if the landing distance does not exceed 5,160 feet for Rwy 19.

OPCION B: The airport may NOT be listed as the destination airport if the landing distance exceeds 5,100 feet for Rwy 19.

OPCION C: The airport may be listed as the destination airport if the landing distance does not exceed 5,350 feet for either runway, wet or dry conditions.

8133 What effective runway length is required for a turbojet-powered airplane at the destination airport if the runways are forecast to be wet or slippery at the ETA? B

OPCION A: 70 percent of the actual runway available, from a height of 50 feet over the threshold.

OPCION B: 115 percent of the runway length required for a dry runway.

OPCION C: 115 percent of the runway length required for a wet runway.

8134 For which of these aircraft is the "clearway" for a particular runway considered in computing takeoff weight limitations? B

OPCION A: Those passenger-carrying transport aircraft certificated between August 26, 1957 and August 30, 1959.

OPCION B: Turbine-engine-powered transport airplanes certificated after September 30, 1958.

OPCION C: U.S. certified air carrier airplanes certificated after August 29, 1959.

8344 How can turbulent air cause an increase in stalling speed of an airfoil? A

OPCION A: An abrupt change in relative wind.

OPCION B: A decrease in angle of attack.

OPCION C: Sudden decrease in load factor.

8369 If an engine failure occurs at an altitude above single-engine ceiling, what airspeed should be maintained? B

OPCION A: Vmc.

OPCION B: Vyse.

OPCION C: Vxse.

8370 What is the resulting performance loss when one engine on a twin-engine fails? B

OPCION A: Reduction of cruise airspeed by 50 percent.

OPCION B: Reduction of climb by 50 percent or more.

OPCION C: Reduction of all performance by 50 percent.

- 8371 Under what condition is Vmc the highest?
OPCION A: Gross weight is at the maximum allowable value.
OPCION B: CG is at the most rearward allowable position.
OPCION C: CG is at the most forward allowable position.

- 8374 What effect does landing at high elevation airports have on groundspeed with comparable conditions relative to temperature, wind, and airplane weight?
OPCION A: Higher than at low elevation.
OPCION B: Lower than at low elevation.
OPCION C: The same as at low elevation.

- 8381 Which maximum range factor decreases as weight decreases?
OPCION A: Angle of attack.
OPCION B: Altitude.
OPCION C: Airspeed.

- 8383 What performance is characteristic of flight at maximum L/D in a propeller-driven airplane?
OPCION A: Maximum range and distance glide.
OPCION B: Best angle of climb.
OPCION C: Maximum endurance.

- 8398 What should a pilot do to maintain "best range" airplane performance when a tailwind is encountered?
OPCION A: Increase speed.
OPCION B: Maintain speed.
OPCION C: Decrease speed.

- 8400 At what speed, with reference to L/Dmax, does maximum rate-of-climb for a jet airplane occur?
OPCION A: A speed greater than that for L/Dmax.
OPCION B: A speed equal to that for L/Dmax.
OPCION C: A speed less than that for L/Dmax.

- 8401 At what speed, with reference to L/Dmax, does maximum range for a jet airplane occur?
OPCION A: A speed less than that for L/Dmax.
OPCION B: A speed equal to that for L/Dmax.
OPCION C: A speed greater than that for L/Dmax.

- 8459 Given the following conditions, what is the minimum torque for takeoff?
A
Pressure altitude 9,000 ft
Tempertaure (OAT) +3°C
Ice vanes Extended
OPCION A: 3,100 foot-pound.
OPCION B: 3,040 foot-pound.
OPCION C: 3,180 foot-pound.

- 8460 Given the following conditions, what is the minimum torque for takeoff?
A
Pressure altitude 7,500 ft
Tempertaure (OAT) +35°C
Ice vanes Retracted
OPCION A: 2,820 foot-pound.
OPCION B: 2,880 foot-pound.
OPCION C: 2,780 foot-pound.

8461 Given the following conditions, what is the minimum torque for takeoff? B

Pressure altitude 7,500 ft
Tempertaure (OAT) +9°C
Ice vanes Extended

OPCION A: 3,200 foot-pound.

OPCION B: 3,160 foot-pound.

OPCION C: 3,330 foot-pound.

8462 Given the following conditions, what is the minimum torque for takeoff? B

Pressure altitude 3,500 ft
Tempertaure (OAT) +43°C
Ice vanes Retracted

OPCION A: 3,000 foot-pound.

OPCION B: 3,050 foot-pound.

OPCION C: 3,110 foot-pound.

8463 Given the following conditions, what is the minimum torque for takeoff? C

Pressure altitude 5,500 ft
Tempertaure (OAT) +29°C
Ice vanes Retracted

OPCION A: 2,950 foot-pound.

OPCION B: 3,100 foot-pound.

OPCION C: 3,200 foot-pound.

8464 Given the following conditions, what is the takeoff distance over a 50-foot obstacle? C

Pressure altitude Sea Level
Tempertaure (OAT) +12°C
Weight 16,000 lb
Wind component 16 kts HW
Ice vanes Extended

OPCION A: 1,750 feet.

OPCION B: 2,800 feet.

OPCION C: 2,550 feet.

8465 Given the following conditions, what is the takeoff ground roll and V1 speed? A

Pressure altitude 4,000 ft
Tempertaure (OAT) 0°C
Weight 15,500 lb
Wind component 16 kts TW
Ice vanes Extended

OPCION A: 2,900 feet, 106 knots.

OPCION B: 4,250 feet, 102 knots.

OPCION C: 2,700 feet, 107 knots.

8466 Given the following conditions, what is the takeoff distance over a 50-foot obstacle? B

Pressure altitude 2,000 ft
Tempertaure (OAT) +15°C
Weight 16,600 lb
Wind component Calm
Ice vanes Retracted

OPCION A: 3,400 feet.

OPCION B: 3,700 feet.

OPCION C: 4,200 feet.

8467 Given the following conditions, what is the takeoff ground roll and V1 speed? A

Pressure altitude 3,000 ft
Tempertaure (OAT) -10°C
Weight 15,000 lb
Wind component 8 kts TW
Ice vanes Extended

OPCION A: 2,200 feet, 105 knots.

OPCION B: 2,000 feet, 113 knots.

OPCION C: 1,900 feet, 103 knots.

8468 Given the following conditions, what is the takeoff distance over a 50-foot obstacle? A

Pressure altitude 6,000 ft
Tempertaure (OAT) +35°C
Weight 14,500 lb
Wind component 10 kts HW
Ice vanes Retracted

OPCION A: 4,150 feet.

OPCION B: 4,550 feet.

OPCION C: 2,600 feet.

8469 Given the following conditions, what is the accelerate-stop field length? C

Pressure altitude 5,000 ft
Tempertaure (OAT) +20°C
Weight 15,000 lb
Wind component 10 kts HW
Ice vanes Retracted

OPCION A: 6,300 feet.

OPCION B: 4,700 feet.

OPCION C: 4,300 feet.

8470 Given the following conditions, what is the accelerate-stop field length? C

Pressure altitude 2,000 ft
Tempertaure (OAT) -15°C
Weight 16,000 lb
Wind component 5 kts HW
Ice vanes Extended

OPCION A: 3,750 feet.

OPCION B: 4,600 feet.

OPCION C: 4,250 feet.

8471 Given the following conditions, what is the accelerate-stop field length? A

Pressure altitude 6,000 ft
Tempertaure (OAT) +10°C
Weight 16,600 lb
Wind component 15 kts HW
Ice vanes Retracted

OPCION A: 4,950 feet.

OPCION B: 4,800 feet.

OPCION C: 5,300 feet.

8472 Given the following conditions, what is the accelerate-stop field length? B

Pressure altitude 8,000 ft
Tempertaure (OAT) -5°C
Weight 14,000 lb
Wind component 4 kts TW
Ice vanes Extended

OPCION A: 4,500 feet.

OPCION B: 4,800 feet.

OPCION C: 5,300 feet.

8473 Given the following conditions, what is the accelerate-stop field length? C

Pressure altitude Sea Level
Tempertaure (OAT) +30°C
Weight 13,500 lb
Wind component 14 kts HW
Ice vanes Retracted

OPCION A: 2,500 feet.

OPCION B: 2,850 feet.

OPCION C: 3,050 feet.

8474 What is the two-engine rate of climb after takeoff in climb configuration for Operating Conditions BE-21? C

OPCION A: 1,350 ft/min.

OPCION B: 2,450 ft/min.

OPCION C: 2,300 ft/min.

8475 What is the single-engine climb gradient after takeoff in climb configuration for Operating Conditions BE-22? C

OPCION A: 6.8 percent gradient.

OPCION B: 7.5 percent gradient.

OPCION C: 5.6 percent gradient.

8476 What is the two-engine rate of climb after takeoff in climb configuration for Operating Conditions BE-23? B

OPCION A: 1,500 ft/min.

OPCION B: 2,600 ft/min.

OPCION C: 2,490 ft/min.

8477 What is the two-engine rate of climb after takeoff in climb configuration for Operating Conditions BE-24? A

OPCION A: 2,100 ft/min.

OPCION B: 2,400 ft/min.

OPCION C: 1,500 ft/min.

8478 What is the single-engine climb gradient after takeoff in climb configuration for Operating Conditions BE-25? C

OPCION A: 385 ft/min.

OPCION B: 780 ft/min.

OPCION C: 665 ft/min.

8479 What are the time, fuel, and distance from the start of climb to cruise altitude for Operating Conditions BE-21? B

OPCION A: 10.0 minutes; 290 pounds; 35 NM.

OPCION B: 10.0 minutes; 165 pounds; 30 NM.

OPCION C: 11.5 minutes; 165 pounds; 30 NM.

8480 What are the time, fuel, and distance from the start of climb to cruise altitude for Operating Conditions BE-22? B

OPCION A: 12.0 minutes; 220 pounds; 40 NM.

OPCION B: 11.0 minutes; 185 pounds; 37 NM.

OPCION C: 10.5 minutes; 175 pounds; 32 NM.

8481 What are the time, fuel, and distance from the start of climb to cruise altitude for Operating Conditions BE-23? B

OPCIÓN A: 13.0 minutes; 180 pounds; 35 NM.

OPCIÓN B: 14.0 minutes; 210 pounds; 40 NM.

OPCIÓN C: 15.0 minutes; 240 pounds; 46 NM.

8482 What are the time, fuel, and distance from the start of climb to cruise altitude for Operating Conditions BE-24? C

OPCIÓN A: 12.0 minutes; 220 pounds; 45 NM.

OPCIÓN B: 9.0 minutes; 185 pounds; 38 NM.

OPCIÓN C: 10.0 minutes; 170 pounds; 30 NM.

8483 What are the time, fuel, and distance from the start of climb to cruise altitude for Operating Conditions BE-25? C

OPCIÓN A: 11.5 minutes; 170 pounds; 31 NM.

OPCIÓN B: 8.0 minutes; 270 pounds; 28 NM.

OPCIÓN C: 12.5 minutes; 195 pounds; 38 NM.

8484 At what altitude is the service ceiling with one engine inoperative for Operating Conditions BE-26? A

OPCIÓN A: 13,000 feet.

OPCIÓN B: 14,200 feet.

OPCIÓN C: 13,600 feet.

8485 Which statement is true regarding performance with one engine inoperative for Operating Conditions BE-27? B

OPCIÓN A: Climb rate at the MEA is more than 50 ft/min.

OPCIÓN B: Service ceiling is below the MEA.

OPCIÓN C: Bleed air OFF improves service ceiling by 3,000 feet.

8486 At what altitude is the service ceiling with one engine inoperative for Operating Conditions BE-28? C

OPCIÓN A: 1,500 feet above the MEA.

OPCIÓN B: 10,400 feet.

OPCIÓN C: 11,800 feet.

8487 Which statement is true regarding performance with one engine inoperative for Operating Conditions BE-29? A

OPCIÓN A: Service ceiling is more than 100 feet above the MEA.

OPCIÓN B: Bleed air must be OFF to obtain a rate of climb of 50 ft/min at the MEA.

OPCIÓN C: Climb is not possible at the MEA.

8488 At what altitude is the service ceiling with one engine inoperative for Operating Conditions BE-30? C

OPCIÓN A: 9,600 feet.

OPCIÓN B: 13,200 feet.

OPCIÓN C: 2,100 feet above the MEA.

8489 What is the en route time of the cruise leg for Operating Conditions BE-31? B

OPCIÓN A: 1 hour 11 minutes.

OPCIÓN B: 1 hour 17 minutes.

OPCIÓN C: 1 hour 19 minutes.

8490 What is the en route time of the cruise leg for Operating Conditions BE-32? A

OPCIÓN A: 1 hour 13 minutes.

OPCIÓN B: 1 hour 15 minutes.

OPCIÓN C: 1 hour 20 minutes.

8491 What is the en route time of the cruise leg for Operating Conditions BE-33? C

OPCIÓN A: 1 hour 50 minutes.

OPCIÓN B: 1 hour 36 minutes.

OPCIÓN C: 1 hour 46 minutes.

8492 What is the en route time of the cruise leg for Operating Conditions BE-34? A

OPCIÓN A: 1 hour 6 minutes.

OPCIÓN B: 1 hour 3 minutes.

OPCIÓN C: 1 hour 11 minutes.

-
- 8493 What is the en route time of the cruise leg for Operating Conditions BE-35? C
- OPCION A:** 1 hour 6 minutes.
OPCION B: 1 hour 8 minutes.
OPCION C: 1 hour 10 minutes.
-
- 8494 What is the fuel consumption during the cruise leg for Operating Conditions BE-31? A
- OPCION A:** 812 pounds.
OPCION B: 749 pounds.
OPCION C: 870 pounds.
-
- 8495 What is the fuel consumption during the cruise leg for Operating Conditions BE-32? C
- OPCION A:** 1,028 pounds.
OPCION B: 896 pounds.
OPCION C: 977 pounds.
-
- 8496 What is the fuel consumption during the cruise leg for Operating Conditions BE-33? B
- OPCION A:** 1,165 pounds.
OPCION B: 1,373 pounds.
OPCION C: 976 pounds.
-
- 8497 What is the fuel consumption during the cruise leg for Operating Conditions BE-34? B
- OPCION A:** 668 pounds.
OPCION B: 718 pounds.
OPCION C: 737 pounds.
-
- 8498 What is the fuel consumption during the cruise leg for Operating Conditions BE-35? C
- OPCION A:** 900 pounds.
OPCION B: 1,030 pounds.
OPCION C: 954 pounds.
-
- 8499 What are the time and distance to descend from 18,000 feet to 2,500 feet? A
- OPCION A:** 10.3 minutes, 39 NM.
OPCION B: 9.8 minutes, 33 NM.
OPCION C: 10.0 minutes, 36 NM.
-
- 8500 What are the distance and fuel consumption to descend from 22,000 feet to 4,500 feet? B
- OPCION A:** 44 NAM, 117 pounds.
OPCION B: 48 NAM, 112 pounds.
OPCION C: 56 NAM, 125 pounds.
-
- 8501 What are the time and distance to descend from 16,500 feet to 3,500 feet? C
- OPCION A:** 9.3 minutes, 37 NAM.
OPCION B: 9.1 minutes, 35 NAM.
OPCION C: 8.7 minutes, 33 NAM.
-
- 8502 What are the distance and fuel consumption to descend from 13,500 feet to 1,500 feet? B
- OPCION A:** 30 NAM, 87 pounds.
OPCION B: 29 NAM, 80 pounds.
OPCION C: 38 NAM, 100 pounds.
-
- 8503 What are the time and distance to descend from 23,000 feet to 600 feet with an average 15-knot headwind? C
- OPCION A:** 14.2 minutes, 50 NAM.
OPCION B: 14.6 minutes, 56 NAM.
OPCION C: 14.9 minutes, 59 NAM.
-
- 8504 What is the landing distance over a 50-foot obstacle for Operating Conditions B-36? A
- OPCION A:** 1,900 feet.
OPCION B: 1,625 feet.
OPCION C: 950 feet.
-

-
- 8505 What are the approach speed and ground roll when landing under Operating Conditions B-36? A
- OPCIÓN A:** 113 knots and 950 feet.
- OPCIÓN B:** 113 knots and 1,950 feet.
- OPCIÓN C:** 112 knots and 900 feet.
-
- 8506 What is the remaining runway length when stopped after landing over a 50-foot obstacle for Operating Conditions B-37? B
- OPCIÓN A:** 2,500 feet.
- OPCIÓN B:** 2,000 feet.
- OPCIÓN C:** 2,600 feet.
-
- 8507 What are the approach speed and ground roll when landing under Operating Conditions B-37? A
- OPCIÓN A:** 108 knots and 1,400 feet.
- OPCIÓN B:** 109 knots and 900 feet.
- OPCIÓN C:** 107 knots and 1,350 feet.
-
- 8508 What is the landing distance over a 50-foot obstacle for Operating Conditions B-38? B
- OPCIÓN A:** 1,850 feet.
- OPCIÓN B:** 1,700 feet.
- OPCIÓN C:** 1,800 feet.
-
- 8509 What is the total runway used when touchdown is at the 1,000 foot marker for Operating Conditions B-38? C
- OPCIÓN A:** 2,000 feet.
- OPCIÓN B:** 1,700 feet.
- OPCIÓN C:** 1,800 feet.
-
- 8510 What is the remaining runway length when stopped after landing over a 50-foot obstacle for Operating Conditions B-39? C
- OPCIÓN A:** 2,300 feet.
- OPCIÓN B:** 2,400 feet.
- OPCIÓN C:** 2,500 feet.
-
- 8511 What are the approach speed and ground roll when landing under Operating Conditions B-39? B
- OPCIÓN A:** 111 knots and 1,550 feet.
- OPCIÓN B:** 110 knots and 1,400 feet.
- OPCIÓN C:** 109 knots and 1,300 feet.
-
- 8512 What is the landing distance over a 50-foot obstacle for Operating Conditions B-40? C
- OPCIÓN A:** 1,500 feet.
- OPCIÓN B:** 1,750 feet.
- OPCIÓN C:** 1,650 feet.
-
- 8553 What is the climb performance with both engines operating? B
- Pressure altitude 9,500 ft
Temperature (OAT) -5°C
Heater ON
- OPCIÓN A:** 925 ft/min.
- OPCIÓN B:** 600 ft/min.
- OPCIÓN C:** 335 ft/min.
-
- 8554 What is the climb performance with both engines operating? B
- Pressure altitude 7,500 ft
Temperature (OAT) +5°C
Heater ON
- OPCIÓN A:** 905 ft/min.
- OPCIÓN B:** 765 ft/min.
- OPCIÓN C:** 1,080 ft/min.
-

8555 What is the climb performance with both engines operating?

B

Pressure altitude 6,500 ft
Temperature (OAT) +25°C
Heater OFF

OPCION A: 285 ft/min.

OPCION B: 600 ft/min.

OPCION C: 400 ft/min.

8556 What is the climb performance with both engines operating?

B

Pressure altitude 11,500 ft
Temperature (OAT) -15°C
Heater ON

OPCION A: 645 ft/min.

OPCION B: 375 ft/min.

OPCION C: 330 ft/min.

8557 What is the climb performance with both engines operating?

A

Pressure altitude 3,500 ft
Temperature (OAT) -10°C
Heater ON

OPCION A: 985 ft/min.

OPCION B: 1,300 ft/min.

OPCION C: 1,360 ft/min.

8558 What is the single-engine climb or descent performance?

A

Pressure altitude 7,500 ft
Temperature (OAT) 0°C

OPCION A: 80 ft/min descent.

OPCION B: 10 ft/min climb.

OPCION C: 50 ft ft/min climb.

8559 Given the following, what is the single-engine climb or descent performance?

C

Pressure altitude 3,000 ft
Temperature (OAT) +35°C

OPCION A: 150 ft/min descent.

OPCION B: 350 ft/min climb.

OPCION C: 100 ft/min descent.

8560 Given the following, what is the single-engine climb or descent performance?

B

Pressure altitude 4,700 ft
Temperature (OAT) +20°C

OPCION A: 420 ft/min climb.

OPCION B: 60 ft/min climb.

OPCION C: 60 ft/min descent.

8561 Given the following, what is the single-engine climb or descent performance?

C

Pressure altitude 9,500 ft
Temperature (OAT) -10°C

OPCION A: 600 ft/min descent.

OPCION B: 840 ft/min descent.

OPCION C: 280 ft/min descent.

8562 Given the following, what is the single-engine climb or descent performance? A

Pressure altitude 1,500 ft
Temperature (OAT) +45°C

- OPCION A:** 100 ft/min descent.
OPCION B: 360 ft/min climb.
OPCION C: 200 ft/min descent.
-

8563 Given the following, what is the airspeed limit (Vne)? A

Gross weight 16,500 lb
Pressure altitude 5,000 ft
Temperature (OAT) -15°C

- OPCION A:** 128 KIAS.
OPCION B: 133 KIAS.
OPCION C: 126 KIAS.
-

8564 What is the airspeed limit (Vne)? B

Gross weight 17,500 lb
Pressure altitude 4,000 ft
Temperature (OAT) +10°C

- OPCION A:** 114 KIAS.
OPCION B: 120 KIAS.
OPCION C: 130 KIAS.
-

8565 What is the airspeed limit (Vne)? A

Gross weight 15,000 lb
Pressure altitude 6,000 ft
Temperature (OAT) 0°C

- OPCION A:** 135 KIAS.
OPCION B: 127 KIAS.
OPCION C: 143 KIAS.
-

8566 What is the airspeed limit (Vne)? A

Gross weight 14,000 lb
Pressure altitude 8,000 ft
Temperature (OAT) -15°C

- OPCION A:** 121 KIAS.
OPCION B: 123 KIAS.
OPCION C: 113 KIAS.
-

8567 What is the airspeed limit (Vne)? C

Gross weight 12,500 lb
Pressure altitude 14,000 ft
Temperature (OAT) -20°C

- OPCION A:** 99 KIAS.
OPCION B: 108 KIAS.
OPCION C: 103 KIAS.
-

8568 What is the single-engine landing distance over a 50-foot obstacle?

C

Gross weight 12,000 lb
Pressure altitude 3,500 ft
Temperature (OAT) +30°C

OPCIÓN A: 850 feet.

OPCIÓN B: 900 feet.

OPCIÓN C: 1,000 feet.

8569 What is the single-engine landing distance over a 50-foot obstacle?

B

Gross weight 16,500 lb
Pressure altitude 5,500 ft
Temperature (OAT) -10°C

OPCIÓN A: 1,700 feet.

OPCIÓN B: 1,550 feet.

OPCIÓN C: 1,600 feet.

8570 What is the single-engine landing distance over a 50-foot obstacle?

A

Gross weight 15,000 lb
Pressure altitude 8,000 ft
Temperature (OAT) +20°C

OPCIÓN A: 1,900 feet.

OPCIÓN B: 1,800 feet.

OPCIÓN C: 2,000 feet.

8571 What is the single-engine landing distance over a 50-foot obstacle?

B

Gross weight 14,000 lb
Pressure altitude 1,000 ft
Temperature (OAT) +10°C

OPCIÓN A: 650 feet.

OPCIÓN B: 920 feet.

OPCIÓN C: 800 feet.

8572 What is the single-engine landing distance over a 50-foot obstacle?

C

Gross weight 17,000 lb
Pressure altitude 4,000 ft
Temperature (OAT) +40°C

OPCIÓN A: 1,850 feet.

OPCIÓN B: 2,200 feet.

OPCIÓN C: 2,000 feet.

8583 What are V1 and Vr speeds for Operating Conditions A-1? (See figures 45, 46, and 47)

A

OPCIÓN A: V1 123.1 knots; Vr 125.2 knots.

OPCIÓN B: V1 120.5 knots; Vr 123.5 knots.

OPCIÓN C: V1 122.3 knots; Vr 124.1 knots.

8584 What are V1 and Vr speeds for Operating Conditions A-2? (See figures 45, 46, and 47)

C

OPCIÓN A: V1 129.7 knots; Vr 134.0 knots.

OPCIÓN B: V1 127.2 knots; Vr 133.2 knots.

OPCIÓN C: V1 127.4 knots; Vr 133.6 knots.

8585 What are V1 and Vr speeds for Operating Conditions A-3? (See figures 45, 46, and 47)

A

OPCIÓN A: V1 136.8 knots; 141.8 knots.

OPCIÓN B: V1 134.8 knots; 139.0 knots.

OPCIÓN C: V1 133.5 knots; 141.0 knots.

8586	What are V1 and Vr speeds for Operating Conditions A-4? (See figures 45, 46, and 47)	B
OPCION A:	V1 128.0 knots; Vr 130.5 knots.	
OPCION B:	V1 129.9 knots; Vr 133.4 knots.	
OPCION C:	V1 128.6 knots; Vr 131.1 knots.	
8587	What are V1 and Vr speeds for Operating Conditions A-5? (See figures 45, 46, and 47)	B
OPCION A:	V1 110.4 knots; Vr 110.9 knots.	
OPCION B:	V1 109.6 knots; Vr 112.7 knots.	
OPCION C:	V1 106.4 knots; Vr 106.4 knots.	
8593	What is the ground distance covered during en route climb for Operating Conditions W-1? (Refer to Figures 48, 49, and 50)	A
OPCION A:	104.0 NM.	
OPCION B:	99.2 NM.	
OPCION C:	109.7 NM.	
8594	What is the ground distance covered during en route climb for Operating Conditions W-2? (Refer to Figures 48, 49, and 50)	C
OPCION A:	85.8 NM.	
OPCION B:	87.8 NM.	
OPCION C:	79.4 NM.	
8595	What is the ground distance covered during en route climb for Operating Conditions W-3? (Refer to Figures 48, 49, and 50)	A
OPCION A:	86.4 NM.	
OPCION B:	84.2 NM.	
OPCION C:	85.1 NM.	
8596	What is the ground distance covered during en route climb for Operating Conditions W-4? (Refer to Figures 48, 49, and 50)	B
OPCION A:	58.4 NM.	
OPCION B:	61.4 NM.	
OPCION C:	60.3 NM.	
8597	What is the ground distance covered during en route climb for Operating Conditions W-5? (Refer to Figures 48, 49, and 50)	C
OPCION A:	68.0 NM.	
OPCION B:	73.9 NM.	
OPCION C:	66.4 NM.	
8598	What is the aircraft weight at the top of climb for Operating Conditions W-1? (Refer to Figures 48, 49, and 50)	B
OPCION A:	81,600 pounds.	
OPCION B:	81,400 pounds.	
OPCION C:	81,550 pounds.	
8599	What is the aircraft weight at the top of climb for Operating Conditions W-2? (Refer to Figures 48, 49, and 50)	C
OPCION A:	82,775 pounds.	
OPCION B:	83,650 pounds.	
OPCION C:	83,800 pounds.	
8600	What is the aircraft weight at the top of climb for Operating Conditions W-3? (Refer to Figures 48, 49, and 50)	B
OPCION A:	75,750 pounds.	
OPCION B:	75,900 pounds.	
OPCION C:	76,100 pounds.	
8601	What is the aircraft weight at the top of climb for Operating Conditions W-4? (Refer to Figures 48, 49, and 50)	B
OPCION A:	86,150 pounds.	
OPCION B:	86,260 pounds.	
OPCION C:	86,450 pounds.	

- 8602 What is the aircraft weight at the top of climb for Operating Conditions W-5? (Refer to Figures 48, 49, and 50) A
OPCIÓN A: 89,900 pounds.
OPCIÓN B: 90,000 pounds.
OPCIÓN C: 90,100 pounds.
- 8603 What is the total time from starting to the alternate through completing the approach for Operating Conditions L-1? B
OPCIÓN A: 30 minutes.
OPCIÓN B: 44 minutes.
OPCIÓN C: 29 minutes.
- 8604 What is the total time from starting to the alternate through completing the approach for Operating Conditions L-2? B
OPCIÓN A: 36 minutes.
OPCIÓN B: 55 minutes.
OPCIÓN C: 40 minutes.
- 8605 What is the total time from starting to the alternate through completing the approach for Operating Conditions L-3? B
OPCIÓN A: 1 hour.
OPCIÓN B: 1 hour 15 minutes.
OPCIÓN C: 1 hour 24 minutes.
- 8606 What is the total time from starting to the alternate through completing the approach for Operating Conditions L-4? A
OPCIÓN A: 35 minutes.
OPCIÓN B: 19 minutes.
OPCIÓN C: 20 minutes.
- 8607 What is the total time from starting to the alternate through completing the approach for Operating Conditions L-5? A
OPCIÓN A: 1 hour 3 minutes.
OPCIÓN B: 48 minutes.
OPCIÓN C: 55 minutes.
- 8608 What is the approximate landing weight for Operating Conditions L-1? C
OPCIÓN A: 79,000 pounds.
OPCIÓN B: 83,600 pounds.
OPCIÓN C: 81,500 pounds.
- 8609 What is the approximate landing weight for Operating Conditions L-2? B
OPCIÓN A: 65,200 pounds.
OPCIÓN B: 65,800 pounds.
OPCIÓN C: 69,600 pounds.
- 8610 What is the approximate landing weight for Operating Conditions L-3? A
OPCIÓN A: 80,300 pounds.
OPCIÓN B: 85,400 pounds.
OPCIÓN C: 77,700 pounds.
- 8611 What is the approximate landing weight for Operating Conditions L-4? A
OPCIÓN A: 73,200 pounds.
OPCIÓN B: 74,190 pounds.
OPCIÓN C: 73,500 pounds.
- 8612 What is the approximate landing weight for Operating Conditions L-5? B
OPCIÓN A: 78,600 pounds.
OPCIÓN B: 77,000 pounds.
OPCIÓN C: 76,300 pounds.

8613	What is the takeoff EPR for Operating Conditions R-1? (See Figures 53, 54, and 55)	C
OPCION A:	2.04.	
OPCION B:	2.01.	
OPCION C:	2.035.	
8614	What is the takeoff EPR for Operating Conditions R-2? (See Figures 53, 54, and 55)	A
OPCION A:	2.19.	
OPCION B:	2.18.	
OPCION C:	2.16.	
8615	What is the takeoff EPR for Operating Conditions R-3? (See Figures 53, 54, and 55)	C
OPCION A:	2.01.	
OPCION B:	2.083.	
OPCION C:	2.04.	
8616	What is the takeoff EPR for Operating Conditions R-4? (See Figures 53, 54, and 55)	B
OPCION A:	2.06.	
OPCION B:	2.105.	
OPCION C:	2.11.	
8617	What is the takeoff EPR for Operating Conditions R-5? (See Figures 53, 54, and 55)	A
OPCION A:	1.98.	
OPCION B:	1.95.	
OPCION C:	1.96.	
8618	What is the takeoff safety speed for Operating Conditions R-1? (See figures 53, 54, and 55)	A
OPCION A:	128 knots.	
OPCION B:	121 knots.	
OPCION C:	133 knots.	
8619	What is the rotation speed for Operating Conditions R-2? (See figures 53, 54, and 55)	C
OPCION A:	147 knots.	
OPCION B:	152 knots.	
OPCION C:	146 knots.	
8620	What are V1, Vr, and V2 speeds for Operating Conditions R-3? (See figures 53, 54, and 55)	B
OPCION A:	143, 143, and 147 knots.	
OPCION B:	138, 138, and 142 knots.	
OPCION C:	136, 138, and 143 knots.	
8621	What are critical engine failure and takeoff safety speeds for Operating Conditions R-4? (See figures 53, 54, and 55)	B
OPCION A:	131 and 133 knots.	
OPCION B:	123 and 134 knots.	
OPCION C:	122 and 130 knots.	
8622	What are rotation and V2 bug speeds for Operating Conditions R-5? (See figures 53, 54, and 55)	A
OPCION A:	138 and 143 knots.	
OPCION B:	136 and 138 knots.	
OPCION C:	134 and 141 knots.	
8628	What is the ground distance covered during en route climb for Operating Conditions V-1? (Refer to Figures 56, 57, and 58)	A
OPCION A:	145 NM.	
OPCION B:	137 NM.	
OPCION C:	134 NM.	

8629 What is the ground distance covered during en route climb for Operating Conditions V-2? (Refer to Figures 56, 57, and 58) C

OPCIÓN A: 84 NM.

OPCIÓN B: 65 NM.

OPCIÓN C: 69 NM.

8630 What is the ground distance covered during en route climb for Operating Conditions V-3? (Refer to Figures 56, 57, and 58) B

OPCIÓN A: 95 NM.

OPCIÓN B: 79 NM.

OPCIÓN C: 57 NM.

8631 What is the ground distance covered during en route climb for Operating Conditions V-4? (Refer to Figures 56, 57, and 58) A

OPCIÓN A: 63 NM.

OPCIÓN B: 53 NM.

OPCIÓN C: 65 NM.

8632 What is the ground distance covered during en route climb for Operating Conditions V-5? (Refer to Figures 56, 57, and 58) C

OPCIÓN A: 70 NM.

OPCIÓN B: 47 NM.

OPCIÓN C: 61 NM.

8633 How much fuel is burned during en route climb for Operating Conditions V-1? (Refer to Figures 56, 57, and 58) C

OPCIÓN A: 4,100 pounds.

OPCIÓN B: 3,600 pounds.

OPCIÓN C: 4,000 pounds.

8634 How much fuel is burned during en route climb for Operating Conditions V-2? (Refer to Figures 56, 57, and 58) A

OPCIÓN A: 2,250 pounds.

OPCIÓN B: 2,600 pounds.

OPCIÓN C: 2,400 pounds.

8635 What is the aircraft weight at the top of climb for Operating Conditions V-3? (Refer to Figures 56, 57, and 58) B

OPCIÓN A: 82,100 pounds.

OPCIÓN B: 82,500 pounds.

OPCIÓN C: 82,200 pounds.

8636 What is the aircraft weight at the top of climb for Operating Conditions V-4? (Refer to Figures 56, 57, and 58) A

OPCIÓN A: 102,900 pounds.

OPCIÓN B: 102,600 pounds.

OPCIÓN C: 103,100 pounds.

8637 What is the aircraft weight at the top of climb for Operating Conditions V-5? (Refer to Figures 56, 57, and 58) A

OPCIÓN A: 73,000 pounds.

OPCIÓN B: 72,900 pounds.

OPCIÓN C: 72,800 pounds.

8638 What is the maximum climb EPR for Operating Conditions T-1? (See Figures 59 and 60) A

OPCIÓN A: 1.82.

OPCIÓN B: 1.96.

OPCIÓN C: 2.04.

8639 What is the maximum climb EPR for Operating Conditions T-2? (See Figures 59 and 60) C

OPCIÓN A: 2.10.

OPCIÓN B: 1.99.

OPCIÓN C: 2.02.

-
- 8640 What is the maximum climb EPR for Operating Conditions T-3? (See Figures 59 and 60) C
OPCION A: 2.11.
OPCION B: 2.02.
OPCION C: 1.90.
-
- 8641 What is the maximum climb EPR for Operating Conditions T-4? (See Figures 59 and 60) C
OPCION A: 2.20.
OPCION B: 2.07.
OPCION C: 2.06.
-
- 8642 What is the maximum climb EPR for Operating Conditions T-5? (See Figures 59 and 60) B
OPCION A: 2.00.
OPCION B: 2.04.
OPCION C: 1.96.
-
- 8643 What is the trip time for Operating Conditions X-1? C
OPCION A: 4 hours 5 minutes.
OPCION B: 4 hours 15 minutes.
OPCION C: 4 hours.
-
- 8644 What is the trip time for Operating Conditions X-2? B
OPCION A: 5 hours 5 minutes.
OPCION B: 6 hours 15 minutes.
OPCION C: 5 hours 55 minutes.
-
- 8645 What is the trip time for Operating Conditions X-3? C
OPCION A: 4 hours 15 minutes.
OPCION B: 3 hours 40 minutes.
OPCION C: 4 hours.
-
- 8646 What is the trip time for Operating Conditions X-4? B
OPCION A: 6 hours 50 minutes.
OPCION B: 5 hours 45 minutes.
OPCION C: 5 hours 30 minutes.
-
- 8647 What is the trip time for Operating Conditions X-5? A
OPCION A: 2 hours 55 minutes.
OPCION B: 3 hours 10 minutes.
OPCION C: 2 hours 50 minutes.
-
- 8648 What is the trip fuel for Operating Conditions X-1? B
OPCION A: 25,000 pounds.
OPCION B: 26,000 pounds.
OPCION C: 24,000 pounds.
-
- 8649 What is the trip fuel for Operating Conditions X-2? C
OPCION A: 33,000 pounds.
OPCION B: 28,000 pounds.
OPCION C: 35,000 pounds.
-
- 8650 What is the trip fuel for Operating Conditions X-3? B
OPCION A: 36,000 pounds.
OPCION B: 34,500 pounds.
OPCION C: 33,000 pounds.
-
- 8651 What is the trip fuel for Operating Conditions X-4? A
OPCION A: 33,000 pounds.
OPCION B: 31,500 pounds.
OPCION C: 34,000 pounds.
-

-
- 8652 What is the trip fuel for Operating Conditions X-5? C
- OPCION A:** 15,000 pounds.
OPCION B: 20,000 pounds.
OPCION C: 19,000 pounds.
-
- 8653 What is the turbulent air penetration N1 power setting for Operating Conditions Q-1? C
- OPCION A:** 82.4 percent?
OPCION B: 84.0 percent.
OPCION C: 84.8 percent.
-
- 8654 What is the turbulent air penetration N1 power setting for Operating Conditions Q-2? B
- OPCION A:** 78.2 percent.
OPCION B: 75.2 percent.
OPCION C: 76.7 percent.
-
- 8655 What is the turbulent air penetration N1 power setting for Operating Conditions Q-3? C
- OPCION A:** 77.8 percent.
OPCION B: 82.6 percent.
OPCION C: 84.2 percent.
-
- 8656 What is the turbulent air penetration N1 power setting for Operating Conditions Q-4? A
- OPCION A:** 76.8 percent.
OPCION B: 75.4 percent.
OPCION C: 74.0 percent.
-
- 8657 What is the turbulent air penetration N1 power setting for Operating Conditions Q-5? A
- OPCION A:** 70.9 percent.
OPCION B: 72.9 percent.
OPCION C: 71.6 percent.
-
- 8658 What is the trip time corrected for wind under Operating Conditions Z-1? B
- OPCION A:** 58.1 minutes.
OPCION B: 51.9 minutes.
OPCION C: 54.7 minutes.
-
- 8659 What is the trip time corrected for wind under Operating Conditions Z-2? C
- OPCION A:** 1 hour 35 minutes.
OPCION B: 1 hour 52 minutes.
OPCION C: 1 hour 46 minutes.
-
- 8660 What is the trip time corrected for wind under Operating Conditions Z-3? B
- OPCION A:** 2 hours 9 minutes.
OPCION B: 1 hour 59 minutes.
OPCION C: 1 hour 52 minutes.
-
- 8661 What is the trip time corrected for wind under Operating Conditions Z-4? B
- OPCION A:** 48.3 minutes.
OPCION B: 50.7 minutes.
OPCION C: 51.3 minutes.
-
- 8662 What is the trip time corrected for wind under Operating Conditions Z-5? A
- OPCION A:** 1 hour 11 minutes.
OPCION B: 56 minutes.
OPCION C: 62 minutes.
-
- 8663 What is the estimated fuel consumption for Operating Conditions Z-1? A
- OPCION A:** 5,230 pounds.
OPCION B: 5,970 pounds.
OPCION C: 5,550 pounds.
-

-
- 8664 What is the estimated fuel consumption for Operating Conditions Z-2? A
OPCION A: 10,270 pounds.
OPCION B: 9,660 pounds.
OPCION C: 10,165 pounds.
- 8665 What is the estimated fuel consumption for Operating Conditions Z-3? B
OPCION A: 12,300 pounds.
OPCION B: 11,300 pounds.
OPCION C: 13,900 pounds.
- 8666 What is the estimated fuel consumption for Operating Conditions Z-4? C
OPCION A: 4,950 pounds.
OPCION B: 5,380 pounds.
OPCION C: 5,230 pounds.
- 8667 What is the estimated fuel consumption for Operating Conditions Z-5? C
OPCION A: 6,250 pounds.
OPCION B: 5,380 pounds.
OPCION C: 7,120 pounds.
- 8668 What are the recommended IAS and EPR settings for holding under Operating Conditions O-1? C
OPCION A: 221 knots and 1.83 EPR.
OPCION B: 223 knots and 2.01 EPR.
OPCION C: 217 knots and 1.81 EPR.
- 8669 What are the recommended IAS and EPR settings for holding under Operating Conditions O-2? B
OPCION A: 210 knots and 1.57 EPR.
OPCION B: 210 knots and 1.515 EPR.
OPCION C: 210 knots and 1.45 EPR.
- 8670 What are the recommended IAS and EPR settings for holding under Operating Conditions O-3? B
OPCION A: 217 knots and 1.50 EPR.
OPCION B: 215 knots and 1.44 EPR.
OPCION C: 216 knots and 1.40 EPR.
- 8671 What are the recommended IAS and EPR settings for holding under Operating Conditions O-4? A
OPCION A: 223 knots and 1.33 EPR.
OPCION B: 225 knots and 1.33 EPR.
OPCION C: 220 knots and 1.28 EPR.
- 8672 What are the recommended IAS and EPR settings for holding under Operating Conditions O-5? C
OPCION A: 219 knots and 1.28 EPR.
OPCION B: 214 knots and 1.26 EPR.
OPCION C: 218 knots and 1.27 EPR.
- 8673 What is the approximate fuel consumed when holding under Operating Conditions O-1? A
OPCION A: 1,625 pounds.
OPCION B: 1,950 pounds.
OPCION C: 2,440 pounds.
- 8674 What is the approximate fuel consumed when holding under Operating Conditions O-2? C
OPCION A: 2,250 pounds.
OPCION B: 2,500 pounds.
OPCION C: 3,000 pounds.
- 8675 What is the approximate fuel consumed when holding under Operating Conditions O-3? A
OPCION A: 2,940 pounds.
OPCION B: 2,520 pounds.
OPCION C: 3,250 pounds.
-

-
- 8676 What is the approximate fuel consumed when holding under Operating Conditions O-4? C
- OPCION A:** 2,870 pounds.
OPCION B: 2,230 pounds.
OPCION C: 1,440 pounds.
-
- 8677 What is the approximate fuel consumed when holding under Operating Conditions O-5? C
- OPCION A:** 2,950 pounds.
OPCION B: 2,870 pounds.
OPCION C: 2,400 pounds.
-
- 8678 How many minutes of dump time is required to reach a weight of 144,500 pounds? B
- Initial weight 180,500 lb
Zero fuel weight 125,500 lb
- OPCION A:** 13 minutes.
OPCION B: 15 minutes.
OPCION C: 16 minutes.
-
- 8679 How many minutes of dump time is required to reduce fuel load to 25,000 pounds? C
- Initial weight 179,500 lb
Zero fuel weight 136,500 lb
- OPCION A:** 10 minutes.
OPCION B: 9 minutes.
OPCION C: 8 minutes.
-
- 8680 How many minutes of dump time is required to reach a weight of 151,500 pounds? C
- Initial weight 181,500 lb
Zero fuel weight 126,000 lb
- OPCION A:** 15 minutes.
OPCION B: 14 minutes.
OPCION C: 13 minutes.
-
- 8681 How many minutes of dump time is required to reduce fuel load to 16,000 pounds? A
- Initial weight 175,500 lb
Zero fuel weight 138,000 lb
- OPCION A:** 9 minutes.
OPCION B: 10 minutes.
OPCION C: 8 minutes.
-
- 8682 What is the approximate level-off pressure altitude after drift-down under Operating Conditions D-1? A
- OPCION A:** 19,400 feet.
OPCION B: 18,000 feet.
OPCION C: 20,200 feet.
-
- 8683 What is the approximate level-off pressure altitude after drift-down under Operating Conditions D-2? B
- OPCION A:** 14,700 feet.
OPCION B: 17,500 feet.
OPCION C: 18,300 feet.
-
- 8684 What is the approximate level-off pressure altitude after drift-down under Operating Conditions D-3? C
- OPCION A:** 22,200 feet.
OPCION B: 19,800 feet.
OPCION C: 21,600 feet.
-

-
- 8685 What is the approximate level-off pressure altitude after drift-down under Operating Conditions D-4? C
OPCION A: 27,900 feet.
OPCION B: 22,200 feet.
OPCION C: 24,400 feet.
-
- 8686 What is the approximate level-off pressure altitude after drift-down under Operating Conditions D-5? B
OPCION A: 8,800 feet.
OPCION B: 9,600 feet.
OPCION C: 13,000 feet.
-
- 8687 What is the go-around EPR for Operating Conditions L-1? B
OPCION A: 2.01 EPR.
OPCION B: 2.03 EPR.
OPCION C: 2.04 EPR.
-
- 8688 What is the go-around EPR for Operating Conditions L-2? C
OPCION A: 2.115 EPR.
OPCION B: 2.10 EPR.
OPCION C: 2.06 EPR.
-
- 8689 What is the go-around EPR for Operating Conditions L-3? A
OPCION A: 2.06 EPR.
OPCION B: 2.07 EPR.
OPCION C: 2.09 EPR.
-
- 8690 What is the go-around EPR for Operating Conditions L-4? A
OPCION A: 2.056 EPR.
OPCION B: 2.12 EPR.
OPCION C: 2.096 EPR.
-
- 8691 What is the go-around EPR for Operating Conditions L-5? A
OPCION A: 2.00 EPR.
OPCION B: 2.04 EPR.
OPCION C: 2.05 EPR.
-
- 8692 What is Vref for Operating Conditions L-1? A
OPCION A: 143 knots.
OPCION B: 144 knots.
OPCION C: 145 knots.
-
- 8693 What is the reference speed for Operating Conditions L-2? B
OPCION A: 140 knots.
OPCION B: 145 knots.
OPCION C: 148 knots.
-
- 8694 What is Vref +20 for Operating Conditions L-3? B
OPCION A: 151 knots.
OPCION B: 169 knots.
OPCION C: 149 knots.
-
- 8695 What is Vref +10 for Operating Conditions L-4? C
OPCION A: 152 knots.
OPCION B: 138 knots.
OPCION C: 148 knots.
-
- 8696 What is the maneuvering speed for Operating Conditions L-5? C
OPCION A: 124 knots.
OPCION B: 137 knots.
OPCION C: 130 knots.
-

-
- 8729 What are the recommended IAS and EPR settings for holding under Operating Conditions H-3? B
- OPCION A:** 226 knots and 1.30 EPR.
OPCION B: 230 knots and 1.31 EPR.
OPCION C: 234 knots and 1.32 EPR.
-
- 8730 What are the recommended IAS and EPR settings for holding under Operating Conditions H-4? B
- OPCION A:** 219 knots and 1.44 EPR.
OPCION B: 216 knots and 1.42 EPR.
OPCION C: 220 knots and 1.63 EPR.
-
- 8731 What are the recommended IAS and EPR settings for holding under Operating Conditions H-5? C
- OPCION A:** 245 knots andn 1.65 EPR.
OPCION B: 237 knots andn 1.61 EPR.
OPCION C: 249 knots andn 1.67 EPR.
-
- 8732 What is the approximate fuel consumed when holding under Operating Conditions H-1? C
- OPCION A:** 3,500 pounds.
OPCION B: 4,680 pounds.
OPCION C: 2,630 pounds.
-
- 8733 What is the approximate fuel consumed when holding under Operating Conditions H-2? A
- OPCION A:** 5,100 pounds.
OPCION B: 3,400 pounds.
OPCION C: 5,250 pounds.
-
- 8734 What is the approximate fuel consumed when holding under Operating Conditions H-3? B
- OPCION A:** 3,090 pounds.
OPCION B: 6,950 pounds.
OPCION C: 6,680 pounds.
-
- 8735 What is the approximate fuel consumed when holding under Operating Conditions H-4? A
- OPCION A:** 3,190 pounds.
OPCION B: 3,050 pounds.
OPCION C: 2,550 pounds.
-
- 8736 What is the approximate fuel consumed when holding under Operating Conditions H-5? C
- OPCION A:** 3,170 pounds.
OPCION B: 7,380 pounds.
OPCION C: 5,540 pounds.
-
- 8737 What are descent time and distance under Operating Conditions S-1? B
- OPCION A:** 24 minutes, 118 NM.
OPCION B: 26 minutes, 125 NM.
OPCION C: 25 minutes, 118 NM.
-
- 8738 What are descent fuel and distance under Operating Conditions S-2? B
- OPCION A:** 1,440 pounds, 104 NM.
OPCION B: 1,500 pounds, 118 NM.
OPCION C: 1,400 pounds, 98 NM.
-
- 8739 What are descent fuel and distance under Operating Conditions S-3? A
- OPCION A:** 1,490 pounds, 118 NM.
OPCION B: 1,440 pounds, 110 NM.
OPCION C: 1,550 pounds, 127 NM.
-
- 8740 What are descent time and distance under Operating Conditions S-4? B
- OPCION A:** 22 minutes, 110 NM.
OPCION B: 21 minutes, 113 NM.
OPCION C: 24 minutes, 129 NM.
-

8741 What are descent fuel and distance under Operating Conditions S-5?

A

OPCIÓN A: 1,420 pounds, 97 NAM.

OPCIÓN B: 1,440 pounds, 102 NAM.

OPCIÓN C: 1,390 pounds, 92 NAM.

8742 Which conditions will result in the shortest landing distance at a weight of 132,500 pounds?

B

OPCIÓN A: Dry runway using brakes and reversers.

OPCIÓN B: Dry runway using brakes and spoilers.

OPCIÓN C: Wet runway using brakes, spoilers and reversers.

8743 How much longer is the dry runway landing distance using brakes only compared to using brakes and reversers at 114,000 pounds gross weight?

C

OPCIÓN A: 1,150 feet.

OPCIÓN B: 500 feet.

OPCIÓN C: 300 feet.

8744 How many feet will remain after landing on a 7,200-foot dry runway with spoilers inoperative at 118,000 pounds gross weight?

B

OPCIÓN A: 4,200 feet.

OPCIÓN B: 4,500 feet.

OPCIÓN C: 4,750 feet.

8745 What is the maximum landing weight which will permit stopping 2,000 feet short of the end of a 5,400-foot dry runway with reversers and spoilers inoperative?

B

OPCIÓN A: 117,500 pounds.

OPCIÓN B: 136,500 pounds.

OPCIÓN C: 139,500 pounds.

8746 Which of the following configurations will result in the shortest landing distance over a 50-foot obstacle to a wet runway?

C

OPCIÓN A: Brakes and spoilers at 122,500 pounds gross weight.

OPCIÓN B: Brakes and reversers at 124,000 pounds gross weight.

OPCIÓN C: Brakes, spoilers, and reversers at 131,000 pounds gross weight.

8747 How many feet will remain after landing on a 6,000-foot wet runway with reversers inoperative at 122,000 pounds gross weight?

B

OPCIÓN A: 2,200 feet.

OPCIÓN B: 2,750 feet.

OPCIÓN C: 3,150 feet.

8748 Which configuration will result in a landing distance of 5,900 feet over a 50 foot obstacle to an icy runway?

C

OPCIÓN A: Use of three reversers at 131,000 pounds gross weight.

OPCIÓN B: Use of brakes and spoilers at 125,000 pounds gross weight.

OPCIÓN C: Use of three reversers at 133,000 pounds gross weight.

8749 What is the transition distance when landing on an icy runway at a gross weight of 134,000 pounds?

A

OPCIÓN A: 400 feet.

OPCIÓN B: 950 feet.

OPCIÓN C: 1,350 feet.

8750 What is the maximum landing weight which will permit stopping 700 feet short of the end of a 5,200-foot icy runway?

B

OPCIÓN A: 124,000 pounds.

OPCIÓN B: 137,000 pounds.

OPCIÓN C: 108,000 pounds.

- 8751 What is the landing distance on an icy runway with reversers inoperative at a landing weight of 125,000 pounds? C
OPCIÓN A: 4,500 feet.
OPCIÓN B: 4,750 feet.
OPCIÓN C: 5,800 feet.
- 8752 How much will landing distance be reduced by using 15° of flaps rather than 0° flaps at a landing weight of 119,000 pounds? B
OPCIÓN A: 500 feet.
OPCIÓN B: 800 feet.
OPCIÓN C: 2,700 feet.
- 8753 What is the ground roll when landing with 15° of flaps at a landing weight of 122,000 pounds? A
OPCIÓN A: 1,750 feet.
OPCIÓN B: 2,200 feet.
OPCIÓN C: 2,750 feet.
- 8754 What approach speed and ground roll will be needed when landing at a weight of 140,000 pounds if flaps are not used? C
OPCIÓN A: 138 knots and 3,900 feet.
OPCIÓN B: 153 knots and 2,900 feet.
OPCIÓN C: 183 knots and 2,900 feet.
- 8755 How much more runway will be used to land with 0° flaps rather than 15° of flaps at a landing weight of 126,000 pounds? A
OPCIÓN A: 900 feet.
OPCIÓN B: 1,800 feet.
OPCIÓN C: 2,700 feet.
- 8756 What approach speed and landing distance will be needed when landing at a weight of 140,000 pounds with 15° of flaps? B
OPCIÓN A: 123 knots and 3,050 feet.
OPCIÓN B: 138 knots and 3,050 feet.
OPCIÓN C: 153 knots and 2,050 feet.
- 8757 What is the maximum charted indicated airspeed while maintaining a 3° glide slope at a weight of 140,000 pounds? C
OPCIÓN A: 127 knots.
OPCIÓN B: 149 knots.
OPCIÓN C: 156 knots.
- 8758 What is the thrust required to maintain a 3° glide slope at 140,000 pounds, with gear down, flaps 30°, and an airspeed of Vref +30 knots? B
OPCIÓN A: 13,300 pounds.
OPCIÓN B: 16,200 pounds.
OPCIÓN C: 17,700 pounds.
- 8759 What thrust is required to maintain level flight at 140,000 pounds, with gear up, flaps 25°, and an airspeed of 172 knots? B
OPCIÓN A: 13,700 pounds.
OPCIÓN B: 18,600 pounds.
OPCIÓN C: 22,000 pounds.
- 8760 What thrust is required to maintain level flight at 140,000 pounds, with gear down, flaps 25°, and an airspeed of 162 knots? B
OPCIÓN A: 17,400 pounds.
OPCIÓN B: 19,500 pounds.
OPCIÓN C: 22,200 pounds.

8761 What thrust is required to maintain level flight at 140,000 pounds, with gear down, flaps 25°, and an airspeed of 145 knots? B

- OPCION A:** 16,500 pounds.
OPCION B: 18,100 pounds.
OPCION C: 18,500 pounds.

8762 What is the change of total drag for a 140,000-pound airplane when configuration is changed from flaps 30°, gear down, to flaps 0°, gear up, at a constant airspeed of 160 knots? A B

- OPCION A:** 13,500 pounds.
OPCION B: 13,300 pounds.
OPCION C: 15,300 pounds.

8763 What is the maximum charted indicated airspeed while maintaining a 3° glide slope at a weight of 110,000 pounds? A

- OPCION A:** 136 knots.
OPCION B: 132 knots.
OPCION C: 139 knots.

8764 What is the thrust required to maintain a 3° glide slope at 110,000 pounds, with gear down, flaps 30°, and an airspeed of Vref +20 knots? B

- OPCION A:** 9,800 pounds.
OPCION B: 11,200 pounds.
OPCION C: 17,000 pounds.

8765 What thrust is required to maintain level flight at 110,000 pounds, with gear down, flaps 40°, and an airspeed of 118 knots? B

- OPCION A:** 17,000 pounds.
OPCION B: 20,800 pounds.
OPCION C: 22,300 pounds.

8766 What thrust is required to maintain level flight at 110,000 pounds, with gear up, flaps 25°, and an airspeed of 152 knots? A

- OPCION A:** 14,500 pounds.
OPCION B: 15,900 pounds.
OPCION C: 16,700 pounds.

8774 The maximum speed during takeoff that the pilot may abort the takeoff and stop the airplane within the accelerate-stop distance is C

- OPCION A:** V2.
OPCION B: Vef.
OPCION C: V1.

8775 The minimum speed during takeoff, following a failure of the critical engine at Vef, at which the pilot may continue the takeoff and achieve the required height above the takeoff surface within the takeoff distance is indicated by symbol B

- OPCION A:** V2min.
OPCION B: V1.
OPCION C: Vlof.

8780 The symbol for the speed at which the critical engine is assumed to fail during takeoff is C

- OPCION A:** V2.
OPCION B: V1.
OPCION C: Vef.

8795 What CAS should be used to maintain the fixed TAS at the proposed altitude? B

- OPCION A:** 157 knots.
OPCION B: 167 knots.
OPCION C: 172 knots.

- 9060 The most important restriction to the operation of turbojet or turboprop engines is B
OPCION A: limiting compressor speed.
OPCION B: limiting exhaust gas temperature.
OPCION C: limiting torque.
- 9061 An outside air pressure decreases, thrust output will C
OPCION A: increase due to greater efficiency of jet aircraft in thin air.
OPCION B: remain the same since compression of inlet air will compensate for any decrease in air pressure.
OPCION C: decrease due to higher density altitude.
- 9062 What effect will an increase in altitude have upon the available equivalent shaft horsepower (ESHP) of a A turboprop engine?
OPCION A: Lower air density and engine mass flow will cause a decrease in power.
OPCION B: Higher propeller efficiency will cause an increase in usable power (ESHP) and thrust.
OPCION C: Power will remain the same but propeller efficiency will decrease.
- 9063 What effect, if any, does high ambient temperature have upon the thrust output of a turbine engine? A
OPCION A: Thrust will be reduced due to the decrease in air density.
OPCION B: Thrust will remain the same, but turbine temperature will be higher.
OPCION C: Thrust will be higher because more heat energy is extracted from the hotter air.
- 9064 What characterizes a transient compressor stall? C
OPCION A: Loud, steady roar accompanied by heavy shuddering.
OPCION B: Sudden loss of thrust accompanied by a loud whine.
OPCION C: Intermittent "bang", as backfires and flow reversals take place.
- 9065 What indicates that a compressor stall has developed and become steady? A
OPCION A: Strong vibrations and loud roar.
OPCION B: Occasional loud "bang" and low reversal.
OPCION C: Complete loss of power with severe reduction in airspeed.
- 9066 Which type of compressor stall has the greatest potential for severe engine damage? C
OPCION A: Intermittent "backfire" stall.
OPCION B: Transient "backfire" stall.
OPCION C: Steady, continuous flow reversal stall.
- 9067 What recovery would be appropriate in the event of compressor stall? A
OPCION A: Reduce fuel flow, reduce angle of attack, and increase airspeed.
OPCION B: Advance throttle, lower angle of attack, and reduce airspeed.
OPCION C: Reduce throttle, reduce airspeed, and increase angle of attack.
- 9068 Under normal operating conditions, which combination of MAP and RPM produce the most severe wear, fatigue, and damage to high performance reciprocating engines? A
OPCION A: High RPM and low MAP.
OPCION B: Low RPM and high MAP.
OPCION C: High RPM and high MAP.
- 9069 What effect does high relative humidity have upon the maximum power output of modern aircraft engines? B
OPCION A: Neither turbojet nor reciprocating engines are affected.
OPCION B: Reciprocating engines will experience a significant loss of BHP.
OPCION C: Turbojet engines will experience a significant loss of thrust.
- 9070 Equivalent shaft horsepower (ESHP) of a turbo-prop engine is a measure of B
OPCION A: turbine inlet temperature.
OPCION B: shaft horsepower and jet thrust.
OPCION C: propeller thrust only.

- 9071 Minimum specific fuel consumption of the turbo-prop engine is normally available in which altitude range? B
OPCION A: 10,000 feet to 25,000 feet.
OPCION B: 25,000 feet to the tropopause.
OPCION C: The tropopause to 45,000 feet.
- 9072 Where is the critical altitude of a supercharged reciprocating engine? A
OPCION A: The highest altitude at which a desired manifold pressure can be obtained.
OPCION B: Highest altitude where the mixture can be leaned to best power ratio.
OPCION C: The altitude at which maximum allowable BMEP can be obtained.
- 9073 What is controlled by the waste gas of a turbo-charged reciprocating engine? B
OPCION A: Supercharger gear ratio.
OPCION B: Exhaust gas discharge.
OPCION C: Throttle opening.
- 9074 How should thrust reversers be applied to reduce landing distance for turbojet aircraft? A
OPCION A: Immediately after ground contact.
OPCION B: Immediately prior to touchdown.
OPCION C: After applying maximum wheel braking.
- 9075 Which condition reduces the required runway for takeoff? C
OPCION A: Higher-than-recommended airspeed before rotation.
OPCION B: Lower-than-standard air density.
OPCION C: Increased headwind component.
- 9076 Which performance factor decreases as airplane gross weight increases, for a given runway? A
OPCION A: Critical engine failure speed.
OPCION B: Rotation speed.
OPCION C: Accelerate-stop distance.
- 9077 Maximum range performance of a turbojet aircraft is obtained by which procedure as aircraft weight reduces? B
OPCION A: Increasing speed or altitude.
OPCION B: Increasing altitude or decreasing speed.
OPCION C: Increasing speed or decreasing altitude.
- 9078 Which procedure produces the minimum fuel consumption for a given leg of the cruise flight? A
OPCION A: Increase speed for a headwind.
OPCION B: Increase speed for a tailwind.
OPCION C: Increase altitude for a headwind, decrease altitude for a tailwind.
- 9079 How should reverse thrust propellers be used during landing for maximum effectiveness in stopping? B
OPCION A: Gradually increase reverse power to maximum as rollout speed decreases.
OPCION B: Use maximum reverse power as soon as possible after touchdown.
OPCION C: Select reverse-pitch after landing and use idle power setting of the engines.
- 9083 What effect does an uphill runway slope have upon takeoff performance? A
OPCION A: Increases takeoff distance.
OPCION B: Decreases takeoff speed.
OPCION C: Decreases takeoff distance.
- 9084 Under which condition during the landing roll are the main wheel brakes at maximum effectiveness? A
OPCION A: When wing lift has been reduced.
OPCION B: At high groundspeeds.
OPCION C: When the wheels are locked and skidding.
- 9085 Which condition has the effect of reducing critical engine failure speed? A
OPCION A: Slush on the runway or inoperative antiskid.
OPCION B: Low gross weight.
OPCION C: High density altitude.

- 9128 What action is appropriate when encountering the first ripple of reported clear air turbulence (CAT)? C
OPCION A: Extend flaps to decrease wing loading.
OPCION B: Extend gear to provide more drag and increase stability.
OPCION C: Adjust airspeed to that recommended for rough air.
- 9129 If severe turbulence is encountered, which procedure is recommended? B
OPCION A: Maintain a constant altitude.
OPCION B: Maintain a constant attitude.
OPCION C: Maintain constant airspeed and altitude.
- 9317 Which is the definition of V2 speed? B
OPCION A: Takeoff decision speed.
OPCION B: Takeoff safety speed.
OPCION C: Minimum takeoff speed.
- 9319 What is the correct symbol for minimum unstick speed? A
OPCION A: Vmu.
OPCION B: Vmd.
OPCION C: Vfc.
- 9320 Which speed symbol indicates the maximum operating limit speed for an airplane? B
OPCION A: Vle.
OPCION B: Vmo/Mmo.
OPCION C: Vlo/Mlo.
- 9321 Which is the correct symbol for design cruising speed? A
OPCION A: Vc.
OPCION B: Vs.
OPCION C: Vma.
- 9322 Which is the correct symbol for the minimum steady-flight speed or stalling speed in the landing configuration? C
OPCION A: Vs.
OPCION B: Vs1.
OPCION C: Vso.
- 9323 Which is correct symbol for the stalling speed or the minimum steady flight speed at which the airplane is controllable? B
OPCION A: Vso.
OPCION B: Vs.
OPCION C: Vs1.
- 9324 What is the name of a plane beyond the end of a runway which does not contain obstructions and can be considered when calculating takeoff performance of turbine-powered aircraft? A
OPCION A: Clearway.
OPCION B: Stopway.
OPCION C: Obstruction clearance plane.
- 9327 What is an area identified by the term "stopway"? B
OPCION A: An area, at least the same width as the runway, capable of supporting an airplane during a normal takeoff.
OPCION B: An area designated for use in decelerating an aborted takeoff.
OPCION C: An area, not as wide as the runway, capable of supporting an airplane during a normal takeoff.
- 9355 Which operational requirement must be observed by a commercial operator when ferrying a large, three-engine, turbojet-powered airplane from one facility to another to repair an inoperative engine? C
OPCION A: The computed takeoff distance to reach V1 must not exceed 70 percent of the effective runway length.
OPCION B: The existing and forecast weather for departure, en route, and approach must be VFR.
OPCION C: No passengers may be carried.

-
- 9560 Estimate the total fuel required to be on the aircraft, prior to taxi at Tucson Int'l. B
- OPCION A:** 2,223 pounds.
- OPCION B:** 2,327 pounds.
- OPCION C:** 2,447 pounds.
-
- 9561 Determine the ETE for the flight from Tucson Int'l to Los Angeles Int'l. B
- OPCION A:** 2 hours 10 minutes.
- OPCION B:** 2 hours 15 minutes.
- OPCION C:** 2 hours 19 minutes.
-
- 9578 (Refer to Figures 107, 115, 116, 117, 118, and 118C) A
- What is the ETE at .78 Mach?
- OPCION A:** 1 hour 08 minutes.
- OPCION B:** 1 hour 02 minutes.
- OPCION C:** 1 hour 05 minutes.
-
- 9579 (Refer to Figures 115, 116, 117, 118, and 118C) B
- What is the total fuel required at .78 Mach?
- OPCION A:** 22,140 pounds.
- OPCION B:** 22,556 pounds.
- OPCION C:** 22,972 pounds.
-
- 9580 (Refer to Figures 115, 116, 117, 118, and 118C) B
- What is the specific range in nautical miles per 1,000 pounds of fuel from level-off to the ARLIN Intersection using .78 Mach?
- OPCION A:** 46.1 NAM/1,000 pounds.
- OPCION B:** 48.2 NAM/1,000 pounds.
- OPCION C:** 50.0 NAM/1,000 pounds.
-
- 9581 (Refer to Figures 115, 116, 117, 118, and 118C) C
- What is the ETE at .80 Mach?
- OPCION A:** 1 hour 02 minutes.
- OPCION B:** 1 hour 04 minutes.
- OPCION C:** 1 hour 07 minutes.
-
- 9582 (Refer to Figures 115, 116, 117, 118, and 118C) B
- What is the total fuel required at .80 Mach?
- OPCION A:** 22,836 pounds.
- OPCION B:** 22,420 pounds.
- OPCION C:** 22,256 pounds.
-
- 9583 (Refer to Figures 115, 116, 117, 118, and 118C) C
- What approximate indicated Mach should be maintained to arrive over the BZA VORTAC 6 minutes after passing IPL VORTAC?
- OPCION A:** .73 Mach.
- OPCION B:** .74 Mach.
- OPCION C:** .715 Mach.
-

9584 (Refer to Figures 107, 115, 116, 117, 118, and 118C)

B

What is the ETE at .82 Mach?

- OPCION A:** 1 hour 05 minutes.
OPCION B: 1 hour 07 minutes.
OPCION C: 1 hour 03 minutes.
-

9585 (Refer to Figures 115, 116, 117, 118, and 118C)

B

What is the total fuel required at .82 Mach?

- OPCION A:** 22,420 pounds.
OPCION B: 22,284 pounds.
OPCION C: 22,700 pounds.
-

9591 What is the ETE from BUF to ORD using .78 Mach?

C

- OPCION A:** 1 hour 09 minutes.
OPCION B: 1 hour 07 minutes.
OPCION C: 1 hour 05 minutes.
-

9592 What is the total fuel required for the flight from BUF to ORD using .78 Mach?

B

- OPCION A:** 19,033 pounds.
OPCION B: 21,739 pounds.
OPCION C: 22,189 pounds.
-

9593 What is the specific range in nautical miles per 1,000 pounds of fuel from level-off to start of descent using .78 Mach?

A

- OPCION A:** 48.8 NAM/1000.
OPCION B: 52.5 NAM/1000.
OPCION C: 55.9 NAM/1000.
-

9594 What is the ETE from BUF to ORD using .80 Mach?

B

- OPCION A:** 1 hour 01 minutes.
OPCION B: 1 hour 04 minutes.
OPCION C: 1 hour 08 minutes.
-

9595 What is the total fuel required for the flight from BUF to ORD using .80 Mach?

C

- OPCION A:** 19,388 pounds.
OPCION B: 22,094 pounds.
OPCION C: 21,644 pounds.
-

9597 (Refer to Figures 158, 159, 160, 160A, 161.)

C

The estimated time en route from STL to LGA for N711JB is

- OPCION A:** 1 hour 46 minutes.
OPCION B: 1 hour 50 minutes.
OPCION C: 1 hour 54 minutes.
-

9598 (Refer to Figures 158, 159, 160, 160A, and 161)

B

The required amount of fuel (in pounds) to be on N711JB, prior to taxi, is

- OPCION A:** 5,993 pounds.
OPCION B: 6,408 pounds.
OPCION C: 6,641 pounds.
-

9610 (Refer to Figures 168, 169, 169A, 171, and 172.)

B

What is the ETE for PTZ 70 from Chicago Pal-Waukee Airport to Greater Buffalo Int'l Airport?

- OPCION A:** 2 hours 15 minutes.
OPCION B: 2 hours 18 minutes.
OPCION C: 2 hours 21 minutes.
-

9611

A

(Refer to Figures 168, 169, 169A, 171, and 172.)

What is the computed fuel usage for PTZ 70 from start or taxi at Chicago Pal-Waukee to landing at Greater Buffalo Int'l?

- OPCION A:** 1,642 pounds.
OPCION B: 2,005 pounds.
OPCION C: 2,550 pounds.
-

9612

C

(Refer to Figures 168, 171, 172, and 173.)

9626

C

(Refer to Figures 179, 180A, 181, 182, and 182A.)

9627

A

(Refer to Figures 179, 180, 181, 182, and 182A.)

9628

B

(Refer to Figures 179, 180, 181, 182, and 183.)

- OPCION A:** 1,132 pounds.
OPCION B: 1,107 pounds.
OPCION C: 1,084 pounds.
-

9635

A

What "TAS" would EAB 90 need to maintain from SWL to SIE in an attempt to cut 3 minutes off of the flight plan (SWL-SIE) ETE?

- OPCION A:** 276.
OPCION B: 280.
OPCION C: 284.
-

9642

A

(Refer to Figures 190, 191, 192, 193, 193A, 194, 195, and 195A.)

- OPCION A:** 1 hour 54 minutes.
OPCION B: 1 hour 57 minutes.
OPCION C: 2 hours 00 minutes.
-

9643 (Refer to Figures 190, 191, 192, 193, 193A, 194, 195, and 195A.)

A

The required fuel that should be onboard PIL 10 at MSP is

- OPCION A:** 28,053 pounds.
OPCION B: 29,057 pounds.
OPCION C: 29,960 pounds.
-

9656 (Refer to Figures 185A, 202, 203, 203A, 204, 205A, and 206.)

B

For PTL 55 to be dispatched on this flight plan (LAS-SFO), how much fuel is required to be onboard at the start of taxi?

- OPCION A:** 27,800 pounds.
OPCION B: 28,317 pounds.
OPCION C: 29,450 pounds.
-

9657 (Refer to Figures 185A, 202, 203, 203A, 204, 205A, and 206.)

C

The ETE on this flight plan (PTL 55 LAS-SFO), is

- OPCION A:** 1 hour 25 minutes.
OPCION B: 1 hour 27 minutes.
OPCION C: 1 hour 29 minutes.
-

9664 In block 3 of the flight plan, there is the following entry: B/B747/R. What does the prefix "B" indicate?

B

- OPCION A:** Foreign air carrier (Brazil).
OPCION B: TCAS and heavy.
OPCION C: DME and transponder but no altitude encoding capability.
-

9665 In block 3 of the flight plan, there is the following entry: B/B747/R. The IR will change to "/I" in February 1999 .What will the "/I" indicate?

B

- OPCION A:** That the flight plan contains an RNAV route
OPCION B: That the flight plan contains an RNAV route.
OPCION C: RNAV/TCAS/Transponder/altitude encoding capability.
-

9676 In block 3 of the flight plan, the G following MD90/indicates the aircraft is equipped with

A

- OPCION A:** GPS/GNSS that has oceanic, en route, terminal, and GPS approach capability.
OPCION B: Traffic Alert and Collision Avoidance System (TCAS) with /R capability.
OPCION C: Electronic Flight Instrument System (EFIS).
-

9677 (Refer to figures 182, 214, 216, 216A, 217, and 218.)

B

The time enroute between BDL and PHL for TNA 90 is

- OPCION A:** 54 minutes.
OPCION B: 52 minutes.
OPCION C: 50 minutes.
-

9678 (Refer to Figures 214, 216, 216A, 217, and 218.)

B

The total fuel required to be onboard TNA 90 before starting to taxi at BDL is

- OPCION A:** 11,979 pounds.
OPCION B: 11,735 pounds.
OPCION C: 11,851 pounds.
-

9679 (Refer to Figures 214, 216, 216A, 217, and 218.)

C

The estimated fuel usage between BDL and PHL for TNA 90 is

- OPCION A:** 10,555 pounds.
OPCION B: 10,799 pounds.
OPCION C: 6,130 pounds.
-